

Declaration of Conformity

We declare under our sole responsibility that the product

Electronic frequency converter

As listed below following the provisions of

Low Voltage Directive 2006/95/EC and the Directive 2004/108/EC

GD 10 - ☐ ☐ ☐ ☐ - ☐ - ☐
1 2 3 4 5

1 – Product series

GD100 – Goodrive100 series

2 –Output power

0R2– 0.2kW

0R4– 0.4kW

0R7– 0.75kW

1R5 – 1.5kW

2R2 – 2.2kW

3 –Torque type

G –Constant torque load

4 –Input voltage level

S2 –single PH 230V

2 – 3PH 230V

4 – 3PH 400V

5 –brake unit

B–optional brake unit

Model No.	Rated Input	Rated Output
GD10-0R2G-S2	singlePH,230V, 47-63Hz,4.9A	3 PH, 0-230V, 0-400Hz, 1.6A, 0.2 kW
GD10-0R2G-S2-B	singlePH,230V, 47-63Hz,4.9A	3 PH, 0-230V, 0-400Hz, 1.6A, 0.2 kW
GD10-0R4G-S2	singlePH,230V, 47-63Hz,6.5A	3 PH, 0-230V, 0-400Hz, 2.5A, 0.4 kW
GD10-0R4G-S2-B	singlePH,230V, 47-63Hz,6.5A	3 PH, 0-230V, 0-400Hz, 2.5A, 0.4 kW
GD10-0R7G-S2	singlePH,230V, 47-63Hz,9.3A	3 PH, 0-230V, 0-400Hz, 4.2A, 0.75 kW
GD10-0R7G-S2-B	singlePH,230V, 47-63Hz,9.3A	3 PH, 0-230V, 0-400Hz, 4.2A, 0.75 kW
GD10-0R2G-2	3PH,230V, 47-63Hz,1.9A	3 PH, 0-230V, 0-400Hz, 1.6A, 0.2 kW
GD10-0R2G-2-B	3PH,230V, 47-63Hz,1.9A	3 PH, 0-230V, 0-400Hz, 1.6A, 0.2 kW
GD10-0R4G-2	3PH,230V, 47-63Hz,2.7A	3 PH, 0-230V, 0-400Hz, 2.5A, 0.4 kW
GD10-0R4G-2-B	3PH,230V, 47-63Hz,2.7A	3 PH, 0-230V, 0-400Hz, 2.5A, 0.4 kW
GD10-0R7G-2	3PH,230V, 47-63Hz,4.9A	3 PH, 0-230V, 0-400Hz, 4.2A, 0.75 kW
GD10-0R7G-2-B	3PH,230V, 47-63Hz,4.9A	3 PH, 0-230V, 0-400Hz, 4.2A, 0.75 kW

GD10-1R5G-S2	singlePH,230V, 47-63Hz,15.7A	3 PH, 0-230V, 0-400Hz, 7.5A, 1.5 kW
GD10-1R5G-S2-B	singlePH,230V, 47-63Hz,15.7A	3 PH, 0-230V, 0-400Hz, 7.5A, 1.5 kW
GD10-2R2G-S2	singlePH,230V, 47-63Hz,24A	3 PH, 0-230V, 0-400Hz, 11A, 2.2 kW
GD10-2R2G-S2-B	singlePH,230V, 47-63Hz,24A	3 PH, 0-230V, 0-400Hz, 11A, 2.2 kW
GD10-1R5G-2	3PH,230V, 47-63Hz,9.0A	3 PH, 0-230V, 0-400Hz, 7.5A, 1.5 kW
GD10-1R5G-2-B	3PH,230V, 47-63Hz,9.0A	3 PH, 0-230V, 0-400Hz, 7.5A, 1.5 kW
GD10-2R2G-2	3PH,230V, 47-63Hz,15A	3 PH, 0-230V, 0-400Hz, 11A, 2.2 kW
GD10-2R2G-2-B	3PH,230V, 47-63Hz,15A	3 PH, 0-230V, 0-400Hz, 11A, 2.2 kW
GD10-0R7G-4	3PH,400V, 47-63Hz,3.2A	3 PH, 0-400V, 0-400Hz, 2.5A, 0.75 kW
GD10-0R7G-4-B	3PH,400V, 47-63Hz,3.2A	3 PH, 0-400V, 0-400Hz, 2.5A, 0.75 kW
GD10-1R5G-4	3PH,400V, 47-63Hz,4.3A	3 PH, 0-400V, 0-400Hz, 4.2A, 1.5 kW
GD10-1R5G-4-B	3PH,400V, 47-63Hz,4.3A	3 PH, 0-400V, 0-400Hz, 4.2A, 1.5 kW
GD10-2R2G-4	3PH,400V, 47-63Hz,7.1A	3 PH, 0-400V, 0-400Hz, 5.5A, 2.2 kW
GD10-2R2G-4-B	3PH,400V, 47-63Hz,7.1A	3 PH, 0-400V, 0-400Hz, 5.5A, 2.2 kW

Appropriate harmonized standard: EN 61800-5-1 :2007 EN 61800-3:2004

Date: 2012.12.26

Sign: [Signature]

(RD general manager)